

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 12/11/2018

Reviewed on 12/11/2018

## 1 Identification

- **Product identifier**
- **Product Name:** Vinyl acetate
- **Part Number:** S-3800
- **Application of the substance / the mixture** Certified Reference Material
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
SPEX CertiPrep, LLC.  
203 Norcross Ave, Metuchen,  
NJ 08840 USA
- **Information department:** product safety department
- **Emergency telephone number:**  
Emergency Phone Number (24 hours)  
CHEMTREC (800-424-9300)  
Outside US: 703-527-3887

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Tox. 3 H331 Toxic if inhaled.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

STOT SE 1 H370 Causes damage to organs.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS06



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

methanol

- **Hazard statements**

H225 Highly flammable liquid and vapor.

H331 Toxic if inhaled.

H351 Suspected of causing cancer.

H370 Causes damage to organs.

- **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

US

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 12/11/2018

Reviewed on 12/11/2018

Product Name: Vinyl acetate

(Contd. of page 1)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

67-56-1	methanol	99.9%
108-05-4	vinyl acetate	0.1%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Remove breathing apparatus only after contaminated clothing have been completely removed.  
In case of irregular breathing or respiratory arrest provide artificial respiration.
- **After inhalation:**  
Supply fresh air or oxygen; call for doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not give anything to eat or drink - Do not induce vomiting
- **Information for Doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.

(Contd. on page 3)

US

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 12/11/2018

Reviewed on 12/11/2018

**Product Name: Vinyl acetate**

(Contd. of page 2)

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**· Protective Action Criteria for Chemicals**

**· PAC-1:**

67-56-1	methanol	530 ppm
108-05-4	vinyl acetate	6.7 ppm

**· PAC-2:**

67-56-1	methanol	2,100 ppm
108-05-4	vinyl acetate	36 ppm

**· PAC-3:**

67-56-1	methanol	7200* ppm
108-05-4	vinyl acetate	180 ppm

## 7 Handling and storage

**· Handling:**

**· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

**· Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

**· Conditions for safe storage, including any incompatibilities**

**· Storage:**

**· Requirements to be met by storerooms and receptacles:** Store in a cool location.

**· Information about storage in one common storage facility:** Not required.

**· Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

**· Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

**· Additional information about design of technical systems:** No further data; see item 7.

**· Control parameters**

**· Components with limit values that require monitoring at the workplace:**

**67-56-1 methanol**

PEL Long-term value: 260 mg/m<sup>3</sup>, 200 ppm

REL Short-term value: 325 mg/m<sup>3</sup>, 250 ppm

Long-term value: 260 mg/m<sup>3</sup>, 200 ppm

Skin

TLV Short-term value: 328 mg/m<sup>3</sup>, 250 ppm

Long-term value: 262 mg/m<sup>3</sup>, 200 ppm

Skin; BEI

**108-05-4 vinyl acetate**

REL Ceiling limit value: 15\* mg/m<sup>3</sup>, 4\* ppm  
\*15-min

TLV Short-term value: 53 mg/m<sup>3</sup>, 15 ppm

Long-term value: 35 mg/m<sup>3</sup>, 10 ppm

**· Ingredients with biological limit values:**

**67-56-1 methanol**

BEI 15 mg/L

Medium: urine

Time: end of shift

Parameter: Methanol (background, nonspecific)

**· Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 4)

Product Name: Vinyl acetate

(Contd. of page 3)

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.
- **Respiratory protection:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

### · Information on basic physical and chemical properties

#### · General Information

#### · Appearance:

**Form:** Liquid  
**Color:** According to product specification

· **Odor:** Characteristic

· **Odour Threshold:** Not applicable.

· **pH-value:** Not applicable.

#### · Change in condition

**Melting point/Melting range:** Undetermined.  
**Boiling point/Boiling range:** 64.7 °C (148.5 °F)

· **Flash point:** < 23 °C (<73.4 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 455 °C (851 °F)

· **Decomposition temperature:** Not applicable.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

#### · Explosion limits:

**Lower:** 5.5 Vol %  
**Upper:** 44 Vol %

· **Vapor pressure at 20 °C (68 °F):** 128 hPa (96 mm Hg)

· **Density at 20 °C (68 °F)** 0.79014 g/cm<sup>3</sup> (6.59372 lbs/gal)

· **Relative density** Not applicable.

· **Vapor density** Not applicable.

· **Evaporation rate** Not applicable.

(Contd. on page 5)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 12/11/2018

Reviewed on 12/11/2018

Product Name: Vinyl acetate

(Contd. of page 4)

- **Solubility in / Miscibility with Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not applicable.
- **Viscosity:**
  - Dynamic:** Not applicable.
  - Kinematic:** Not applicable.
- **Solvent content:**
  - Organic solvents:** 99.9 %
  - VOC content:** 99.90 %
- **Solids content:** 0.0 %
- **Other information** No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**67-56-1 methanol**

Oral	LD50	5,628 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Toxic

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

108-05-4	vinyl acetate	2B
----------	---------------	----

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 6)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 12/11/2018

Reviewed on 12/11/2018

Product Name: Vinyl acetate









(Contd. of page 5)

· *Other adverse effects* No further relevant information available.

### 13 Disposal considerations

- *Waste treatment methods*
- *Recommendation:* Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- *Uncleaned packagings:*
- *Recommendation:* Disposal must be made according to official regulations.

### 14 Transport information

· <i>UN-Number</i> · <i>DOT, ADR, IMDG, IATA</i>	UN1230
· <i>UN proper shipping name</i> · <i>DOT</i> · <i>ADR</i> · <i>IMDG, IATA</i>	Methanol 1230 Methanol METHANOL
· <i>Transport hazard class(es)</i> · <i>DOT</i>	
 	
· <i>Class</i> · <i>Label</i>	3 Flammable liquids 3, 6.1
· <i>ADR</i>	
 	
· <i>Class</i> · <i>Label</i>	3 Flammable liquids 3+6.1
· <i>IMDG</i>	
 	
· <i>Class</i> · <i>Label</i>	3 Flammable liquids 3/6.1
· <i>IATA</i>	
 	
· <i>Class</i> · <i>Label</i>	3 Flammable liquids 3 (6.1)
· <i>Packing group</i> · <i>DOT, ADR, IMDG, IATA</i>	II
· <i>Environmental hazards:</i>	Not applicable.
· <i>Special precautions for user</i> · <i>Danger code (Kemler):</i> · <i>EMS Number:</i> · <i>Stowage Category</i> · <i>Stowage Code</i>	Warning: Flammable liquids 336 F-E,S-D B SW2 Clear of living quarters.

(Contd. on page 7)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 12/11/2018

Reviewed on 12/11/2018

Product Name: Vinyl acetate

(Contd. of page 6)

· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 1230 METHANOL, 3 (6.1), II

### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 313 (Specific toxic chemical listings):**

All ingredients are listed.

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

67-56-1 | methanol

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

108-05-4 | vinyl acetate

A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02



GHS06



GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

methanol

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H331 Toxic if inhaled.

H351 Suspected of causing cancer.

H370 Causes damage to organs.

· **Precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

(Contd. on page 8)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 12/11/2018

Reviewed on 12/11/2018

**Product Name: Vinyl acetate**

(Contd. of page 7)

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Use explosion-proof electrical/ventilating/lighting/equipment.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 Store locked up.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.  
 • **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

• **Department issuing SDS:** product safety department

• **Contact:**

SPEX CertiPrep, LLC.

1-732-549-7144

• **Date of preparation / last revision** 12/11/2018 / -

• **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 3: Acute toxicity – Category 3

Carc. 2: Carcinogenicity – Category 2

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

US